



Using the DashHawk for the CASE Relearn (CAN vehicles only)

NOTE: Be advised engine coolant temperature must be at least 158 degrees before performing the relearn.

1. Plug small end of cable into right side of DashHawk.
2. Plug connector end into vehicle's Data Link Connector port, located under the driver's side dash*.
3. Place key in ignition and turn forward.
4. DashHawk will illuminate, after splash screens you will see sensor readings.
5. Press **MENU**.
6. Use the up and down arrows to select **DIAGNOSTICS**. Then click **ENTER**.
7. Use the up and down arrows to select **GM OPTIONS**. Then click **ENTER**.
8. Use the up and down arrows to select **CASE RELEARN** at the bottom. Then click **ENTER**.
9. Follow instructions on the DashHawk screen.
 - a. Start engine. Press **ENTER** to continue.
 - b. Set parking brake. Press **ENTER** to continue.
 - c. Step on brake firmly. Press **ENTER** to continue.
 - d. CASE Relearn command will now be sent. Press **ENTER** to continue.
 - e. Rev engine until it hits the rev limiter, and take your foot off the pedal.
 - f. CASE Relearn will be completed when the next screen indicates as such.
10. When finished, turn the vehicle off for 15 seconds, and then remove the Dash Hawk.

*Data Link Connector End (Vehicle side)

Will be located underneath driver's side dash.

